

EverGrip® LSC19 Cable Extensions

Molded 6-Circuit Multi-Cable Extensions



Five year limited warranty



Features & Benefits:

- Thermoplastic resin premold creates a bond between the cable and connector for superior strain relief and secure terminations
- Pins and sockets cannot push back, extending life of the connector
- Rugged construction helps prevent broken conductors and loose or damaged ground rings
- Keyed design prevents misalignment of circuit conductors and unmateable or mismatched connections
- Thermoplastic elastomer overmold absorbs impact and provides an insulated and secure gripping surface for easier mating and safe handling
- Multi-cables carry 6-circuits of lighting power inside a single jacket, avoiding 6 individual runs of cable
- Specially formulated PVC jacket provides exceptional flexibility and durability
- Available for 1.5 mm² and 2.5 mm² cable
- “Tempered spring” female contacts maintain constant pin pressure to help ensure low resistance connections
- Silver-plated brass contacts for high conductivity
- All black construction blends into scenery and is ideal for stage or studio lighting applications

Rating	Male/Female Connector	Cable	Catalog No.
16 Amp, 240 VAC Maximum (6-Circuit)	Molded Lex 6-Circuit	H07RN-F 3G x 1.5mm ²	EGME-18G-1.5-XX
16 Amp, 240 VAC Maximum (6-Circuit) Ground Conductors Bonded	Molded Lex 6-Circuit	H07RN-F 3G x 2.5mm ²	EGME-18G-2.5-XX

XX in catalog number to specify cable length.

Contact : Lex Products Ltd
Tel. : +44(0)1592 210000
info@lexproducts.co.uk
www.lexproducts.co.uk

EverGrip® Fan-Ins and Fan-Outs

Molded 6-Circuit Multi-Cable Extensions



Fan-In female
LSC19 to (6) male



Black Version

Fan-Out male
LSC19 to (6)
female



Black Version

Features & Benefits:

- Thermoplastic resin premold creates a bond between the cable and connector for superior strain relief and secure terminations
- Pins and sockets cannot push back, extending the life of the connectors
- Rugged construction helps prevent broken conductors and loose or damaged ground rings
- Keyed design prevents misalignment of circuit conductors and unmateable or mismatched connections
- Thermoplastic elastomer overmold absorbs impact and provides an insulated and secure gripping surface for easier mating and safe handling
- Silver-plated brass contacts for high conductivity
- Also available with a variety of Duraplug, Permaplug or Schuko connectors
- All black construction blends into scenery and is ideal for stage or studio lighting applications
- C-FORM connectors are also available in black

Fan-Ins

Rating	Male Connector	Cable	Female Connector	Catalog No. *
16 Amp, 240 VAC	C-FORM 16 Amp, 200 VAC - 250 VAC IP44	H07RN-F 3G x 1.5mm ²	Molded Lex LSC19	EGFI-1-16A CFORM BLU-1M
16 Amp, 240 VAC	C-FORM 16 Amp, 200 VAC - 250 VAC IP44	H07RN-F 3G x 2.5mm ²	Molded Lex LSC19	EGFI-2-16A CFORM BLU-1M

Fan-Outs

Rating	Male Connector	Cable	Female Connector	Catalog No. *
16 Amp, 240 VAC	Molded Lex LSC19	H07RN-F 3G x 1.5mm ²	C-FORM 16 Amp, 200 VAC - 250 VAC IP44	EGFO-1-16A CFORM BLU-1M
16 Amp, 240 VAC	Molded Lex LSC19	H07RN-F 3G x 2.5mm ²	C-FORM 16 Amp, 200 VAC - 250 VAC IP44	EGFO-2-16A CFORM BLU-1M

Custom Lengths available. Contact sales.

* - Also available with black connectors. Replace suffix "BLU" Blue with "BLK" Black for black connectors.

Contact : Lex Products Ltd
Unit 2A Frances Industrial Park
Wemyss Road
Dysart
Kirkcaldy
KY1 2XZ
Tel. : +44(0)1592 210000
info@lexproducts.co.uk
www.lexproducts.co.uk